sigma-aldrich.com

SAFETY DATA SHEET

Version 5.5 Revision Date 09/08/2014 Print Date 09/15/2014

1. PRODUCT	AND COMPANY	IDENTIFICATION	

1.1	Product identifiers Product name	:	Benzyl chloride
	Product Number Brand	:	185558 Aldrich
	CAS-No.	:	100-44-7
1.2	Relevant identified uses of	of th	e substance or mixture and uses advised against
	Identified uses	:	Laboratory chemicals, Manufacture of substances
1.3	Details of the supplier of	the	safety data sheet
	Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
	Telephone Fax	:	+1 800-325-5832 +1 800-325-5052

1.4 **Emergency telephone number**

Emergency Phone # : (314) 776-6555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 4), H227 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 3), H331 Skin irritation (Category 2), H315 Serious eye damage (Category 1), H318 Skin sensitisation (Category 1), H317 Germ cell mutagenicity (Category 1B), H340 Carcinogenicity (Category 1B), H350 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Specific target organ toxicity - repeated exposure (Category 2), H373

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word	Danger
Hazard statement(s) H227 H302 H315 H317 H318 H331	Combustible liquid. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic if inhaled.
105550	

H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/ physician.
P321	Specific treatment (see supplemental first aid instructions on this label).
P330	Rinse mouth.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for
	extinction.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS Lachrymator.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances Synonyms	: a-Chlorotoluene
Formula	: C ₇ H ₇ Cl
Molecular weight	: 126.58 g/mol
CAS-No.	: 100-44-7
Registration number	: 01-2119480483-35-XXXX

Hazardous components

Component	Classification	Concentration
Benzyl chloride		
	Flam. Liq. 4; Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye Dam. 1; Skin Sens. 1; Carc. 1B; STOT SE 3; STOT RE 2; H227, H302, H315, H317, H318, H331, H335, H350, H373	90 - 100 %
Methyloxirane Included in the Cand Regulation (EC) No. 1907/2006 (REA	idate List of Substances of Very High Concern (SV ACH)	(HC) according to
	Flam. Liq. 1; Acute Tox. 4; Acute Tox. 3; Skin Irrit. 2; Eye	1 - 5 %
- 185558		

3.1

	Dam. 1; Muta. 1B; Carc. 1B; STOT SE 3; Aquatic Acute 3; Aquatic Chronic 3; H224, H302, H311 + H331, H315, H318, H335, H340, H350, H412	
--	---	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Continue rinsing eyes during transport to hospital.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides, Hydrogen chloride gas

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Light sensitive. Moisture sensitive.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control	Basis		
			parameters			
Benzyl chloride	100-44-7	TWA	1 ppm	USA. ACGIH Threshold Limit Values (TLV)		
	Remarks	Upper Res	spiratory Tract irrita	ation		
		Eye irritati	on			
		Skin irritat	ion			
		Confirmed	Confirmed animal carcinogen with unknown relevance to humans			
		С	1 ppm	USA. NIOSH Recommended		
			5 mg/m3	Exposure Limits		
		15 minute	ceiling value			
		TWA	1 ppm	USA. Occupational Exposure Limits		
			5 mg/m3	(OSHA) - Table Z-1 Limits for Air		
				Contaminants		
		The value	The value in mg/m3 is approximate.			
		TWA	1 ppm	USA. OSHA - TABLE Z-1 Limits for		
			5 mg/m3	Air Contaminants - 1910.1000		
Methyloxirane	75-56-9	TWA	2 ppm	USA. ACGIH Threshold Limit Values (TLV)		
		Eye & Upp	per Respiratory Tra	act irritation		
				n with unknown relevance to humans		
		Sensitizer				
		Potential Occupational Carcinogen				
			See Appendix A			
		TWA	100 ppm	USA. Occupational Exposure Limits		
			240 mg/m3	(OSHA) - Table Z-1 Limits for Air		
				Contaminants		
		The value	The value in mg/m3 is approximate.			
		TWA	20 ppm	USA. OSHA - TABLE Z-1 Limits for		
			50 mg/m3	Air Contaminants - 1910.1000		

8.2 Exposure controls

Appropriate engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Eye/face protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	pungent
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -43 °C (-45 °F) - lit.
f)	Initial boiling point and boiling range	177 - 181 °C (351 - 358 °F) - lit.
g)	Flash point	67 °C (153 °F)
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 14 %(V) Lower explosion limit: 1.1 %(V)
k)	Vapour pressure	1.60 hPa (1.20 mmHg) at 25 °C (77 °F)
l) Aldrich - 185	Vapour density	4.37 - (Air = 1.0)

	Deletion lessel	
m)	Relative density	1.1 g/cm3 at 25 °C (77 °F)
n)	Water solubility	0.46 g/l at 30 °C (86 °F) - Decomposes in contact with water.
o)	Partition coefficient: n- octanol/water	log Pow: 2.3
p)	Auto-ignition temperature	585 °C (1,085 °F) at 1,030 hPa (773 mmHg)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	er safety information	
	Surface tension	37.8 mN/m at 20 °C (68 °F)
	Relative vapour density	4.37 - (Air = 1.0)

10. STABILITY AND REACTIVITY

10.1 Reactivity

9.2

No data available

10.2 Chemical stability

Stable under recommended storage conditions. Contains the following stabiliser(s): Methyloxirane (<=1 %)

- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** Heat, flames and sparks.

10.5 Incompatible materials

Contact with common metals (except nickel and lead) or moisture produces a Friedel-Crafts, condensation-type reaction with the liberation of heat and formation of toxic and corrosive hydrogen chloride. Hydrolyzes very slowly to form hydrogen chloride and benzyl alcohol. This product is not sensitive to physical impact. When stabilized with propylene oxide, the possibility of a Friedel-Crafts type reaction is minimized. Depletion of the stabilizer increases the possibility of condensation reactions, Oxidizing agents, Iron and iron salts., Brass, Aluminum

10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 560 mg/kg (OECD Test Guideline 401)

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

Skin - Rabbit Result: Irritating to skin. - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

- Mouse Result: May cause sensitisation by skin contact. (OECD Test Guideline 429)

Germ cell mutagenicity

S. typhimurium Result: This material has shown a positive Ames test, an in vitro test that indicates a possible potential to produce a carcinogenic effect.

Mutagenicity (micronucleus test) Mouse Result: negative

Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

IARC: 2A - Group 2A: Probably carcinogenic to humans (Benzyl chloride)

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Methyloxirane)

- NTP: Reasonably anticipated to be a human carcinogen (Methyloxirane)
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: XS8925000

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence Liver - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence (Methyloxirane)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish	LC50 - Danio rerio (zebra fish) - 4 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	Immobilization EC50 - Daphnia magna (Water flea) - 6.1 mg/l - 48 h (OECD Test Guideline 202)

Toxicity to algae

Growth inhibition EC50 - Pseudokirchneriella subcapitata (aglae) - 19.3 mg/l - 72 h

(OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d Result: 71 % - Readily biodegradable. (OECD Test Guideline 301C)

12.3 Bioaccumulative potential No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

	RANSPORT INFORMA	TION				
	DOT (US) UN number: 1738 Proper shipping name: Reportable Quantity (F Marine pollutant: No Poison Inhalation Haza	RQ): 100 lbs	Packing group: I	I		
	IMDG UN number: 1738 Proper shipping name: Marine pollutant: No	Class: 6.1 (8) BENZYL CHLORIDE	Packing group: I	I E	MS-No: F-A, S-B	
	IATA UN number: 1738 Proper shipping name:	Class: 6.1 (8) Benzyl chloride	Packing group: I	I		
. RI	EGULATORY INFORM	ATION				
	Methyloxirane	nts ents are subject to reportir	ng levels establish	CAŚ-No. 75-56-9	Revision Date 2008-11-03	
	Benzyl chloride			100-44-7	2007-07-01	
	SARA 313 Compone The following compon	nts ents are subject to reportir	ng levels establish	ied by SARA 1 CAS-No.	itle III, Section 313: Revision Date	
	Methyloxirane			75-56-9	2008-11-03	

15.

Benzyl chloride	100-44-7	2007-07-01
SARA 311/312 Hazards Fire Hazard, Acute Health Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
Benzyl chloride Methyloxirane	CAS-No. 100-44-7 75-56-9	Revision Date 2007-07-01 2008-11-03
Pennsylvania Right To Know Components		
Benzyl chloride Methyloxirane	CAS-No. 100-44-7 75-56-9	Revision Date 2007-07-01 2008-11-03
New Jersey Right To Know Components		
Benzyl chloride Methyloxirane	CAS-No. 100-44-7 75-56-9	Revision Date 2007-07-01 2008-11-03
California Prop. 65 Components WARNING! This product contains a chemical known to the State of California to cause cancer. Methyloxirane Benzyl chloride	CAS-No. 75-56-9 100-44-7	Revision Date 2007-09-28 2007-09-28

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Carc.	Carcinogenicity
Eye Dam.	Serious eye damage
Flam. Liq.	Flammable liquids
H224	Extremely flammable liquid and vapour.
H227	Combustible liquid.
H302	Harmful if swallowed.
H311 + H331	Toxic in contact with skin or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Muta.	Germ cell mutagenicity
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
0.0.02	

HMIS Rating

Health hazard:	3
Chronic Health Hazard:	*
Flammability:	2
Physical Hazard	0

NFPA Rating

Health hazard:	3
Fire Hazard:	2
Reactivity Hazard:	0

Further information

Copyright 2014 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.5

Revision Date: 09/08/2014

Print Date: 09/15/2014