#### MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

Product Name OfficeMax® Compressed Gas Duster

**Synonym(s)**Model # OM96090
Model #: OM96091

Model #: OM96091 Model #: OM96092

Model #: Model #

CAS # Mixture
Product use Dust control

Manufacturer Falcon Safety Products, Inc.

25 Imclone Drive

Branchburg, NJ 08876 US Phone: 1-800-498-7192

Supplier OfficeMax

263 Shuman Blvd Naperville, IL 60563 US Phone 1-630-438-7800

LEGEND
HMIS/NFPA

Severe 4
Serious 3
Moderate 2
Slight 1
Minimal 0





## 2. Hazards Identification

Emergency overview DANGER

Flammable gas. Contents under pressure. Containers may explode when heated.

Potential short term health effects

Routes of exposure Eye, Skin contact, Inhalation.

Eyes Contact with liquid may cause frostbite.

Skin Contact with liquid may cause frostbite.

**Inhalation** Excessive intentional inhalation may cause respiratory tract irritation and central

nervous system effects (headache, dizziness). Vapors may cause dizziness or

suffocation.

IngestionNot a normal route of exposure.Target organsEyes. Skin. Respiratory system.

Chronic effects Prolonged or repeated exposure can cause drying, defatting and dermatitis.

Signs and symptoms Symptoms may include redness, edema, drying, defatting and cracking of the skin.

# 3. Composition / Information on Ingredients

Ingredient(s)	CAS#	Percent
Ethane, 1,1-difluoro-	75-37-6	60 - 100

#### 4. First Aid Measures

First aid procedures

Eye contact Immediately flush with cool water. Remove contact lenses, if applicable, and continue

flushing for 15 minutes. Obtain medical attention immediately.

**Skin contact** Flush with cool water. Wash with soap and water. Obtain medical attention if irritation

persists.

Inhalation If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately. Do not induce vomiting. Never give anything by mouth if victim is unconscious, or is Ingestion convulsing. Obtain medical attention. General advice Do not puncture or incinerate container. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children. 5. Fire Fighting Measures Flammable by WHMIS/OSHA criteria. Containers may explode when heated. Flammable properties Extinguishing media Suitable extinguishing media Do not extinguish burning gas if flow cannot be shut off immediately. Use water spray or fog nozzle to keep cylinder cool Small Fires: Dry chemical. Carbon dioxide. Water spray. Fog. Unsuitable extinguishing media Not available Protection of firefighters Specific hazards arising from Contents under pressure. Pressurized container may explode when exposed to heat or the chemical flame. Cool containers with flooding quantities of water until well after fire is out. Protective equipment for Firefighters should wear full protective clothing including self contained breathing firefighters apparatus. **Hazardous combustion products** May include and are not limited to: Oxides of carbon. Fluoride gases. **Explosion data** Not available Sensitivity to mechanical impact Not available Sensitivity to static discharge 6. Accidental Release Measures Personal precautions Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Methods for containment Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. Before attempting clean up, refer to hazard data given above. Remove sources of Methods for cleaning up ignition. Although the chance of a significant spill or leak is unlikely in aerosol containers, in the event of such an occurrence, absorb spilled material with a non-flammable absorbent such as sand or vermiculite. 7. Handling and Storage Avoid breathing mists or aerosols of this product. Use good industrial hygiene practices Handling in handling this material. Keep out of reach of children. Do not store at temperatures above 49 °C (120.2°F). Storage Keep away from heat, open flames or other sources of ignition. 8. Exposure Controls / Personal Protection **Exposure limits** Ingredient(s) **Exposure Limits** Ethane, 1,1-difluoro-**ACGIH-TLV** Not established **OSHA-PEL** Not established **Engineering controls** Use only under good ventilation conditions or with respiratory protection. Personal protective equipment Wear safety glasses with side shields. Eye / face protection

**Hand protection** If there is constant skin contact, rubber gloves are recommended.

**Skin and body protection** As required by employer code.

**Respiratory protection** Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands and face before breaks and immediately after handling the

product.

## 9. Physical and Chemical Properties

AppearanceClear.ColorColorlessFormLiquefied gasOdorSlight ethereal.Odor thresholdNot available

Physical state Gas

pH Not applicable

Melting point Not available

Freezing point Not available

Boiling point -25 °C (-13.00 °F)

Flash point -50 °C (-58.00 °F)

Pour point Not available

Evaporation rate Not available

Flammability limits in air, lower, %

by volume

3.9

Flammability limits in air, upper, %

by volume

16.9

Vapor pressure 599.43 kPa @25°C Vapor density 2.4 @25°C (air=1)

Specific gravity 0.91

Relative density 0.9 g/cc @25°C

Octanol/water coefficient Not available

Solubility (H2O) Slightly

Auto-ignition temperature 454 °C (849.20 °F)

Percent volatile 100

## 10. Stability and Reactivity

Chemical stability Stable under recommended storage conditions.

Conditions to avoid Aerosol containers are unstable at temperatures above 49°C (120.2°F).

**Incompatible materials** Alkaline materials. Alkaline earth metals.

Hazardous decomposition products May include and are not limited to: Oxides of carbon. Fluoride gases.

Possibility of hazardous reactions Hazardous polymerization does not occur.

#### 11. Toxicological Information

Component analysis - LC50

Ingredient(s) LC50

Ethane, 1,1-difluoro- > 64000 ppm rat

Component analysis - Oral LD50

Ingredient(s) LD50

Ethane, 1,1-difluoro- 1500 mg/kg rat

Effects of acute exposure

Eye Contact with liquid may cause frostbite.

Skin Contact with liquid may cause frostbite.

#19638 Page 3 of 6 Issue date 28-Oct-2009

**Inhalation** Excessive intentional inhalation may cause respiratory tract irritation and central

nervous system effects (headache, dizziness). Vapors may cause dizziness or

suffocation.

**Ingestion** Not a normal route of exposure.

SensitizationNon-hazardous by WHMIS/OSHA criteria.Chronic effectsNon-hazardous by WHMIS/OSHA criteria.CarcinogenicityNon-hazardous by WHMIS/OSHA criteria.MutagenicityNon-hazardous by WHMIS/OSHA criteria.Reproductive effectsNon-hazardous by WHMIS/OSHA criteria.TeratogenicityNon-hazardous by WHMIS/OSHA criteria.

Synergistic Materials Not available

# 12. Ecological Information

Not available **Ecotoxicity** Not available **Environmental effects** Aquatic toxicity Not available Persistence / degradability Not available Not available Bioaccumulation / accumulation Partition coefficient Not available Mobility in environmental media Not available Chemical fate information Not available Not available Other adverse effects

## 13. Disposal Considerations

Waste codes Not available

Disposal instructions Review feder

Waste from residues / unused

products

Review federal, state/provincial, and local government requirements prior to disposal.

Not available

Contaminated packaging Not available

# 14. Transport Information

#### **U.S. Department of Transportation (DOT)**

Basic shipping requirements:

Proper shipping name 1,1-Difluoroethane

Hazard class 2.1 UN number 1030

Additional information:

Packaging exceptions ORM-D (applicable to containers up to 1 L)



**Transportation of Dangerous Goods (TDG - Canada)** 

Basic shipping requirements:

**Proper shipping name** 1,1-Difluoroethane

Hazard class 2.1 UN number 1030

Additional information:

Packaging exceptions Limited quantity (containers up to 125mL)



IATA/ICAO (Air)

Basic shipping requirements:

Proper shipping name 1,1-Difluoroethane

Hazard class 2.1 UN number 1030

Additional information:

Maximum net quantity

packaging

Forbidden



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled

Products Regulations and the MSDS contains all the information required by the

Controlled Products Regulations.

Canada - CEPA - Schedule I - List of Toxic Substances

Ethane, 1,1-difluoro- 75-37-6 Totally halogenated chlorofluorocarbons that have the molecular formula CnClxF(2n+2-x):

(a) quantities that may be manufactured or imported; (b) Prohibition on manufacture, use, sale, offer for sale, import or export except for authorized uses [SOR/89-351, s. 16;

90-453, s. 5; 94-408, s. 24; 92-507, s. 17; 96-237, s. 5]

US Federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

chemical

Yes

**CERCLA (Superfund) reportable quantity** 

None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely

hazardous substance

Section 311 hazardous chemical Yes

Clean Air Act (CAA)

Clean Water Act (CWA)

Not available

Not available

WHMIS status Controlled

WHMIS classification Class A - Compressed Gas, Class B - Division 1 - Flammable Gas

WHMIS labeling





State regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

U.S. - Louisiana - Reportable Quantity List for Pollutants

Ethane, 1,1-difluoro- 75-37-6 5000 Lb final RQ; 2270 kg final RQ

U.S. - Massachusetts - Right To Know List

Ethane, 1,1-difluoro- 75-37-6 Present **U.S. - New Jersey - Right to Know Hazardous Substance List** Ethane, 1,1-difluoro- 75-37-6 sn 0715

Inventory name

Country(s) or regionInventory nameOn inventory (yes/no)\*CanadaDomestic Substances List (DSL)YesCanadaNon-Domestic Substances List (NDSL)NoUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

#### 16. Other Information

Disclaimer Information contained herein was obtained from sources considered technically accurate

and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the

use of or reliance on any information contained in this document.

 Issue date
 28-Oct-2009

 Effective date
 15-Oct-2009

 Expiry date
 15-Oct-2012

Prepared by Dell Tech Laboratories Ltd. (519) 858-5021

Other information For an updated MSDS, please contact the supplier/manufacturer listed on the first

page of the document.