

	1. Product and Company Identification		
Product number	875-006		
Product name	Dust Up Floor Dressing & Dust Mop Treatment		
Effective date	27-Apr-2011		
Company information	Claire Mfg. 1005 Westgate Addison, IL 60101 United States		
Company phone	General Assistance 630-543-7600		
Emergency telephone US	800-424-9300		
Emergency telephone outside US	703-527-3887		
Version #	on # 08		
Supersedes date	03-Feb-2011		
	2. Hazards Identification		
Emergency overview	Aerosol. FLAMMABLE Will be easily ignited by heat, spark or flames. CONTENTS UNDER PRESSURE. Prolonged exposure may cause chronic effects.		
Potential health effects			
Routes of exposure	Eye contact. Inhalation. Skin contact. Ingestion.		
Eyes	Contact with liquid or mist will irritate the eyes.		
Skin	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.		
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.		
Ingestion	Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.		
Target organs	Central nervous system. Lungs.		
Chronic effects	May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.		
Signs and symptoms	Discomfort in the chest. Narcosis. Coughing. Defatting of the skin. Skin irritation.		

3. Composition / Information on Ingredients			
Components	CAS #	Percent	
Paraffinic, Naphthenic Solvent	64742-47-8	70 - 80	
Propane	74-98-6	8 - 10	
Odorless Mineral Spirits	64742-48-9	5 - 8	
Non-hazardous and other components below reportable levels		10 - 20	

4. First Aid Measures		
First aid procedures		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.	
Skin contact	Wash off with warm water and soap. Get medical attention if irritation develops and persists.	
Inhalation	Move to fresh air. Get medical attention immediately.	
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not induce vomiting without advice from poison control center.	

Product name: Dust Up Floor Dressing & Dust Mop Treatment Product #: 875 Dust Up Floor Dressing & Dust Mop Treatment

cause fire or explosion hazard. Exinguishing media Suitable extinguishing media Suitable extinguishing media Specific hazards arising from the chemical Protective equipment and precautions for firefighters Stop leak if you can do so without risk. Move the cylinder to a sale and open area if th leak is irreparable. Stop the flow of material, if this is without risk. Swater spray to reduce vapors of divert your of could with water to prevent you professure build up. Cool containers with flooding quantities of water with will after fire is out. Aethods for containment Eventods for cleaning up Aethods for cleaning up The test of the sale and open area if th leak is irreparable. Stop the flow of material, if this is without risk. Water spray to reduce vapors of divert your of could with leak is lineparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors of divert your of could with leak is lineparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors of divert your cloud and place into a container for later disposal. Small Splits: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly with water.			5. Fire Fighting Me			
Suitable extinguishing media Protection of firefighters Water spray. Water fog. Dry chemical. Carbon dioxide (CO2). Specific hazards arising from the chemical Protective equipment and precautions for firefighters Fire may produce irritating, corrosive and/or toxic gases. In case of fire and/or explosion do not breathe fumes. Containers should be cooled wit water to the end of the and/or explosion do not breathe fumes. Containers with flooding quantities of water to the end of the and/or explosion do not breathe fumes. Containers with flooding quantities of water to the end of the and/or explosion do not breathe fumes. Containers should be cooled wit water to the end of the end of the end of the reduce vapors of divert vapor cloud diff. Rethods for cleaning up Stop leak if you can do so without risk. Move the cylinder to a sale and open area if th leak is irreparable. Stop the flood of material, if this is without risk. Use water spray to reduce vapors of divert vapor cloud diff. Rethods for cleaning up Stop leak if you can do so without risk. Move the cylinder to a sale and open area if the leaks is treparable. Stop the flood dut and place lino a container for later disposal. Rethods for cleaning up Should not be released into the environment. Use a non-combustible material like water. Rethods for cleaning up Should not be released into the environment. Use a non-combustible material like variation and the environment. Use a dispray but is an other as untrace thoroughly to remove residual contata with skin. Avoid contat with eyes. Wear personal protective	Flammable properties			ant ignition sources and flas	sh back. Runoff to sewer may	
Protection of firefighters Fire may produce initialing, corrosive and/or toxic gases. Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled will water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out. Aethods for containment C. Accidental Release Measures Aethods for cleaning up Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is imparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Aethods for cleaning up Should no the released in to the environment. Use a non-combustible material like verniculite, sand or earth to sak up the product and place into a container for later disposal. Small Splits: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area throughly with water. Image: Pressurized container: Do not pierce or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn, even after use. Do not smoke with using or difference or burn	Extinguishing media					
the chemical Protective equipment and precautions for firefighters In case of fire and/or explosion do not breathe fumes. Containers should be cooled win water on preserve build up. Cool containers with flooding quantities of water unit well after fire is out. Rethods for containment 6. Accidental Release Measures Stop leak if you can do so without risk. Move the cylinder to a safe and open area if th leak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or diver vapor cloud diff. Atchods for cleaning up Should not be released into the environment. Use a non-combusible material like verticuitile, sand or earth to soak up the product and place into a container for later disposal. Should not be released into the environment. Use a non-combusible material like thoroughly to remove residual contamination. After removal flush contaminated area thoroughly to the verticuiting is shoroughly diry. Use only in area provided with appropriate exhaust venilation. Do no use if spray button is missing or defective. Do not not evolue empty containers. Avoid contact with syst. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food dirk and animal feedingstuffs. Levi 3 Aerosol. Storage Contents under pressure to top prinkles. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food dirk and animal feedingstuffs. Levi 3 Aerosol. Storage CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established <tr< td=""><td></td><td>dia Water. V</td><td>Vater spray. Water fog. D</td><td>Dry chemical. Carbon dioxic</td><td>le (CO2).</td></tr<>		dia Water. V	Vater spray. Water fog. D	Dry chemical. Carbon dioxic	le (CO2).	
precautions for firefighters water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out. Rethods for containment Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or diver vapor cloud drift. Aethods for cleaning up Should not be released into the environment. Use a non-combustible material like verniculite, sand or earth to soak up the product and place into a container for later disposal. Small Splits: Wipe up with absorbert material (e.g. cloh, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water. Itandling Pressurized container. Do not pierce or burn, even after use. Do not smoke while usit or until sprayed surface is thoroughly dry. Use only in rear provided with appropriate entry on the sub exposure. Storage Contents under pressure. Do not purcture, inclinerate or rush. The pressure in sealer containers can increase under the influence of heat. Keep away from food drink and animal feedingstuffs. Level 3 Aerosol. Exposure limits CAS # TWA STEL Ceiling Propane 74.98-6 1000 ppm Not established Not established OSHA Components CAS # TWA STEL Ceiling Propane 74.98-6		om Fire may	v produce irritating, corro	sive and/or toxic gases.		
Archive and the set of the set o		s water to				
Iteak is irreparable. Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor could drift. Alethods for cleaning up Should not be released into the environment. Use a non-combustible material like vermicullie, sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly to remove residual contamination. After removal flush contaminated area thoroughly to remove residual contamination. After removal flush contaminated area thoroughly to remove residual contamination. After removal flush contaminated area thoroughly to remove residual contamination. After removal flush contaminated area thoroughly to remove residual contamination. After removal flush contaminers are noticed water. Itandling Pressurized container: Do not pierce or burn, even after use. Do not smoke while usin or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Storage Contents under pressure. Do not		6. A	Accidental Release	Measures		
vermiculitic sand or earth to soak up the product and place into a container for later disposal. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water. Image: the standing of the standi	Methods for containment	leak is ir				
thoroughly with water. 7. Handling and Storage Pressurized container: Do not pierce or burn, even after use. Do not smoke while usin or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid con	Methods for cleaning up	vermicul	ite, sand or earth to soal			
Handling Pressurized container: Do not piece or burn, even after use. Do not smoke while usin or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with sin. Avoid contact with eyes. Wear presonal protective equipment. Avoid prolonged exposure. Storage Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and source of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food drink and animal feedingstuffs. Level 3 Aerosol. Exposure limits ACGIH Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established OSHA Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established Personal protection Chemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place. Respiratory protection Chemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place. Respirat		thorough	nly to remove residual co	pent material (e.g. cloth, fle ntamination. After removal	ece). Clean surface flush contaminated area	
or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilitation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid contact with eyes. Wear personal protective equipment. Avoid protonged exposure. Storage Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and source of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food drink and animal feedingstuffs. Level 3 Aerosol. Storage CAS # TWA			7. Handling and St	torage		
or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilitation. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid contact with skin. Avoid contact with eyes. Wear personal protective equipment. Avoid protonged exposure. Storage Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat and source of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food drink and animal feedingstuffs. Level 3 Aerosol. Storage CAS # TWA	Handling	Pressuri	zed container. Do not pi	erce or burn even after us	e. Do not smoke while using	
Containers can increase under the influence of heat. Keep away from heat and source of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food drink and animal feedingstuffs. Level 3 Aerosol. Suppose the exposure controls / Personal Protection Exposure Controls / Personal Protection Exposure limits ACGIH CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established OSHA Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established Personal protective equipment Eye / face protection Skin protection Chemical goggles are recommended. Skin protection Choose body protection according to the amount and concentration of the dangerous substance at the work place. Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. OPhysical & Chemical Properties Appearance		or until s exhaust empty co	prayed surface is thorou ventilation. Do not use if ontainers. Avoid contact	ghly dry. Use only in area p spray button is missing or with skin. Avoid contact wit	provided with appropriate defective. Do not re-use	
Exposure limits ACGIH Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established OSHA Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established OSHA Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established Propane 74-98-6 1000 ppm Not established Not established Personal protective equipment Eye / face protection Chemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place. Respiratory protection Choose body protection according to the amount and concentration of the dangerous substance at the work place. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. 9. Physical & Chemical Properties Soliding point 410 °F (210 °C) estimated	Storage	containe of ignitio area equ	rs can increase under th n. Avoid exposure to lon upped with sprinklers. Ke	e influence of heat. Keep a g periods of sunlight. Store eep out of the reach of child	way from heat and sources in cool place. Keep in an	
ACGIH TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established OSHA Cas # TWA STEL Ceiling OSHA Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established Propane 74-98-6 1000 ppm Not established Not established Personal protective equipment Eye / face protection Chemical goggles are recommended. Not established Skin protection Choose body protection according to the amount and concentration of the dangerous substance at the work place. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. Spearance Compressed liquefied gas. 410 °F (210 °C) estimated		8. Expos	ure Controls / Pers	onal Protection		
ComponentsCAS #TWASTELCeilingPropane74-98-61000 ppmNot establishedNot establishedOSHA ComponentsCAS #TWASTELCeilingPropane74-98-61000 ppmNot establishedNot establishedPropane74-98-61000 ppmNot establishedNot establishedPersonal protective equipment Eye / face protection Skin protectionChemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place.Not established levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.Respiratory protection9. Physical & Chemical PropertiesStep PropertiesAppearance Boiling pointCompressed liquefied gas. 410 °F (210 °C) estimatedStep PropertiesStep Properties	Exposure limits					
Propane 74-98-6 1000 ppm Not established Not established OSHA Components CAS # TWA STEL Ceiling Propane 74-98-6 1000 ppm Not established Not established Propane 74-98-6 1000 ppm Not established Not established Personal protective equipment Eye / face protection Chemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place. Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. 9. Physical & Chemical Properties Appearance Compressed liquefied gas. 410 °F (210 °C) estimated		CAS #	TWA	STEL	Ceiling	
ComponentsCAS #TWASTELCeilingPropane74-98-61000 ppmNot establishedNot establishedPersonal protective equipment Eye / face protection Skin protectionChemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place.Choose body protection according to the amount and concentration of the dangerous appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.Appearance Boiling pointCompressed liquefied gas. 410 °F (210 °C) estimatedSTELCeiling						
ComponentsCAS #TWASTELCeilingPropane74-98-61000 ppmNot establishedNot establishedPersonal protective equipment Eye / face protection Skin protectionChemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place.Choose body protection according to the amount and concentration of the dangerous appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.Appearance Boiling pointCompressed liquefied gas. 410 °F (210 °C) estimatedSTELCeiling	OSHA					
Propane 74-98-6 1000 ppm Not established Not established Personal protective equipment Eye / face protection Chemical goggles are recommended. Not established Skin protection Chemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. Physical & Chemical Properties Appearance Compressed liquefied gas. Boiling point 410 °F (210 °C) estimated		CAS #	TWA	STEL	Ceiling	
Eye / face protection Skin protectionChemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place.Respiratory protectionWhen workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.Physical & Chemical PropertiesAppearance Boiling pointCompressed liquefied gas. 410 °F (210 °C) estimated		74-98-6	1000 ppm	Not established		
Eye / face protection Skin protectionChemical goggles are recommended. Choose body protection according to the amount and concentration of the dangerous substance at the work place.Respiratory protectionWhen workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.Physical & Chemical PropertiesAppearance Boiling pointCompressed liquefied gas. 410 °F (210 °C) estimated	Personal protective equinment	t				
Skin protection Choose body protection according to the amount and concentration of the dangerous substance at the work place. Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. 9. Physical & Chemical Properties Appearance Compressed liquefied gas. Boiling point 410 °F (210 °C) estimated			al goggles are recommer	nded.		
Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. 9. Physical & Chemical Properties Appearance Compressed liquefied gas. 80iling point 410 °F (210 °C) estimated		Choose body protection according to the amount and concentration of the dangerous				
AppearanceCompressed liquefied gas.Boiling point410 °F (210 °C) estimated	Skin protection		ce at the work place.			
Boiling point 410 °F (210 °C) estimated	-	substand When we appropri	orkers are facing concen ate certified respirators.	If permissible levels are exc	ceeded use NIOSH	
	-	substand When w appropri mechani	orkers are facing concen ate certified respirators. ical filter / organic vapor	If permissible levels are exc cartridge or an air-supplied	ceeded use NIOSH	
	-	substand When w appropri mechani 9. Pł	orkers are facing concen ate certified respirators. ical filter / organic vapor nysical & Chemical	If permissible levels are exc cartridge or an air-supplied	ceeded use NIOSH	
	Respiratory protection	substand When we appropri mechani 9. Pt Compres	orkers are facing concen ate certified respirators. ical filter / organic vapor hysical & Chemical ssed liquefied gas.	If permissible levels are exc cartridge or an air-supplied	ceeded use NIOSH	

Product name: Dust Up Floor Dressing & Dust Mop Treatment Product #: 875 Dust Up Floor Dressing & Dust Mop Treatment

_	0.7704		
Density	0.7731 g/cm3 estimated		
Flammability (HOC)	39.1415 kJ/g estimated No		
Flash back			
Flash point	-156 °F (-104.4 °C) Propellant		
Form	Aerosol.		
Freezing point	Not available		
Odor	Solvent. fruity		
pH Discribulator	Not applicable		
Physical state	Liquid.		
Pressure	35 - 50 psig @ 70F		
Solubility	Negligible		
Specific gravity	0.7732 es	stimated	
	10. Chemica	al Stability & Reactivity Information	
Chemical stability	Risk of ig	nition.	
Conditions to avoid	Heat, flam	nes and sparks.	
Hazardous decomposition prod	lucts No hazar	dous decomposition products are known.	
	11.	Toxicological Information	
Acute effects	Acute LD	50: 2606 mg/kg estimated, Rat, Dermal	
Component analysis - LD50			
Toxicology Data - Selected LD	50s and LC50s		
Odorless Mineral Spirits	64742-48-9	Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >3160 mg/kg	
Paraffinic, Naphthenic Solvent	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg	
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h	
	1:	2. Ecological Information	
Ecotoxicity	EC50 229	76 mg/L estimated, Fish, 96.00 Hours, 984 mg/L estimated, Daphnia, 48.00 Hours, a substance which causes risk of hazardous effects to the environment.	
	13	. Disposal Considerations	
Waste codes	D001: Wa	aste Flammable material with a flash point <140 F	
Disposal instructions	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.		
	1	4. Transport Information	
Department of Transportation (DOT) Requirem	ents	
Basic shipping requiremen	· ·		
Proper shipping name	Consumer commodity		
Hazard class	ORM-D		
Subsidiary hazard class	None		
Additional information:			
Packaging exceptions	156, 306		
Packaging non bulk	156, 306		
Packaging bulk	None		

Proper chinning name	ts:		
Proper shipping name	AEROSC	DLS	
Hazard class	2.1		
UN number	1950		/ - \
Additional information:			
Packaging exceptions	LTD QTY	, ,	
Labels required	None		2
ATA			
Basic shipping requirement	ts:		
Proper shipping name		flammable	
Hazard class	2.1		
UN number	1950		
Additional information:			
Packaging exceptions	LTD QTY	,	
Labels required	2.1		2
			V
	1;	5. Regulatory Information	
IS federal regulations		luct is a "Hazardous Chemical" as defined by the OS	HA Hazard Communication
		, 29 CFR 1910.1200. /SARA Hazardous Substances - Not applicable.	
Occupational Safety and Health	Administration	n (OSHA)	
29 CFR 1910.1200 hazardou chemical	is Yes		
CERCLA (Superfund) reportable	e quantity		
None			
Superfund Amendments and Re	authorization /	Act of 1986 (SARA)	
Section 302 extremely hazardous substance	No		
Section 311 hazardous cher	mical Yes		
Hazard categories (311/312)	Delayed I Fire Haza Pressure	e Hazard - Yes Hazard - Yes ard - Yes Hazard - Yes / Hazard - No	
nventory status			
nventory status Country(s) or region	Inventory na	me	On inventory (yes/no)*
-	-	me ixisting Chemical Substances in China (IECSC)	
Country(s) or region	Inventory of E		No
Country(s) or region China	Inventory of E European Inve	xisting Chemical Substances in China (IECSC)	No Yes
Country(s) or region China Europe	Inventory of E European Inve European List	ixisting Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS)	No Yes Yes
Country(s) or region China Europe Europe	Inventory of E European Inve European List Inventory of E	Existing Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS) t of Notified Chemical Substances (ELINCS)	No Yes Yes No
Country(s) or region China Europe Europe Japan Korea United States & Puerto Rico	Inventory of E European Inve European List Inventory of E Existing Chen Toxic Substar	Existing Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS) t of Notified Chemical Substances (ELINCS) Existing and New Chemical Substances (ENCS)	No Yes Yes No No Yes
Country(s) or region China Europe Europe Japan Korea United States & Puerto Rico A "Yes" indicates that all compone	Inventory of E European Inve European List Inventory of E Existing Chen Toxic Substar	Existing Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS) t of Notified Chemical Substances (ELINCS) Existing and New Chemical Substances (ENCS) nicals List (ECL) nces Control Act (TSCA) Inventory	No Yes Yes No No Yes
Country(s) or region China Europe Europe Japan Korea United States & Puerto Rico A "Yes" indicates that all compone	Inventory of E European Inve European List Inventory of E Existing Chen Toxic Substar	Existing Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS) t of Notified Chemical Substances (ELINCS) Existing and New Chemical Substances (ENCS) nicals List (ECL) nces Control Act (TSCA) Inventory	No Yes Yes No No Yes
Country(s) or region China Europe Europe Japan Korea United States & Puerto Rico A "Yes" indicates that all compon State regulations U.S Pennsylvania - RTK (Righ Odorless Mineral Spirits Paraffinic, Naphthenic Solvent	Inventory of E European Inve European List Inventory of E Existing Chen Toxic Substar nents of this produc ht to Know) List 64742-48-9 64742-47-8	Existing Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS) t of Notified Chemical Substances (ELINCS) Existing and New Chemical Substances (ENCS) nicals List (ECL) nces Control Act (TSCA) Inventory ct comply with the inventory requirements administered by Present Present	No Yes Yes No No Yes
China Europe Europe Japan Korea United States & Puerto Rico A "Yes" indicates that all compone State regulations U.S Pennsylvania - RTK (Righ Odorless Mineral Spirits	Inventory of E European Inve European List Inventory of E Existing Chen Toxic Substar nents of this product ht to Know) List 64742-48-9	Existing Chemical Substances in China (IECSC) entory of New and Existing Chemicals (EINECS) t of Notified Chemical Substances (ELINCS) Existing and New Chemical Substances (ENCS) nicals List (ECL) nces Control Act (TSCA) Inventory ct comply with the inventory requirements administered by Present	On inventory (yes/no)* No Yes Yes No No Yes the governing country(s)

Product name: Dust Up Floor Dressing & Dust Mop Treatment Product #: 875 Dust Up Floor Dressing & Dust Mop Treatment

HMIS® ratings	Health: 1* Flammability: 4 Physical hazard: 0
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication, The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
MSDS sections updated	Product and Company Identification: Product and Company Identification Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Physical & Chemical Properties
Prepared by	Regulatory Compliance