> Back to North American SDS list Non Toxic Premixed & Dry Glazes

North American Format

SECTION 1: COMPANY & PRODUCT IDENTIFICATION

Prepalked/ember 4, 2010

Supersedes:August 1, 2010Manufacturer:Coloramics, LLC (D.B.A. Mayco Colors)

4077 Weaver Court South

Hilliard, Ohio 43026

United States of America

(614) 876-1171

IN CASE OF EMERGENCY PLEASE CONTACT YOUR REGIONAL POISON CONTROL CENTER

Product Identification: Ceramic Glazes

Product Usage: Glazing of ceramic ware

Product Lines Covered by this Safety Data Sheet:

Ast	roASe5m19	Theoptiumal	A39a548

Classic Crackles		CC-101 through CC-108
Clear Glaze		S-2101, C-300, S-2000, NT-CLR
Crystalites Crystal Glaz	е	S-2701 through S-2732
Crystalline Glazes		CR-100 through CR-301
Elements		EL-101 through EL-137
Elements Chunkies		EL-201 through EL-212
Foundations		FN-001 through FN-306
	1	

Jungle Gems

(Unleaded Formulas) | CG-707 through CG-977

Pottery Cascades PC-601, PC-602, PC-603, PC-604

Raku RK-100 through RK-107

Specialty Glazes SG-101, SG-201, SG-202, SG-302, SG-401, SG-501

Speckled Stroke & Coat SP-201 through SP-279

Stroke & Coat SC-01 through SC-94

Stoneware Glazes SW-100 through SW-253, SW-001 through SW-003

SD-100 through SD-253, SD-001 through SW-003

Stoneware Washes
Stroke & Coat Accents
Discontinued Products
SW-301 through SW-304
SA-001, SA-002, SA-003
One Strokes: all

Pottery Coats: PC-501 through PC-505
Pottery Stuccos: PS-551 through PS-555
Series 2000: S-2102 through S-2593

Crystalites: S-2710, S-2717, S-2720, S-2721, S-2722

Specialty Glazes: SG-102, SG-301, SG-303, SLG-17, SLG-2, SLG-6

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Clow to High Silica (Quartz)	Ingredients	CAS	% of Formula	
Calcium Carbonate 471-34-1 0% - 3% Frit (lead free) 65997-18-4 21% - 55% Various Pigments Confidential Varies Kaolin/Clay 1332-58-7 2% - 7% Zinc Oxide 1314-13-2 0% - 1% Carboxymethylcellulose 9004-32-4 0% - 1½%	(Low to High)			-
Frit (lead free) 65997-18-4 21% - 55% Various Pigments Confidential Varies Kaolin/Clay 1332-58-7 2% - 7% Zinc Oxide 1314-13-2 0% - 1% Carboxymethylcellulose 9004-32-4 0% - 1½%	Silica (Quartz)	14808-60-7	1% - 3%	
Various Pigments Confidential Varies Kaolin/Clay 1332-58-7 2% - 7% Zinc Oxide 1314-13-2 0% - 1% Carboxymethylcellulose 9004-32-4 0% - 1½%	Calcium Carbonate	471-34-1	0% - 3%	
Kaolin/Clay 1332-58-7 2% - 7% Zinc Oxide 1314-13-2 0% - 1% Carboxymethylcellulose 9004-32-4 0% - 1½%	Frit (lead free)	65997-18-4	21% - 55%	
Zinc Oxide 1314-13-2 0% - 1% Carboxymethylcellulose 9004-32-4 0% - 1½%	Various Pigments	Confidential	Varies	
Carboxymethylcellulose 9004-32-4 0% - 1½%	Kaolin/Clay	1332-58-7	2% - 7%	
	Zinc Oxide	1314-13-2	0% - 1%	
Nonholino Svenito 37244 96 5 0% 13%	Carboxymethylcellulo	se 9004-32-4	0% - 11/2%	
Nephenile Syenite 37244-30-3 0 % - 13 %	Nepheline Syenite	37244-96-5	0% - 13%	
Zirconium Silicate (Zr Si O) 10101-57-7	Zirconium Silicate (Zr	Şi O)	10101-57-7

Water	7732-18-5	Varies

SECTION 3: HAZARDS IDENTIFICATION

Crystalline silica dust will be present when using dry mix products and may be present if unfired, dried glaze is excessively handled and allowed to create dust.

Mists from spraying may contain crystalline silica.

Route(s) of Entry: Inhalation, Ingestion; absorption through the skin is negligible.

Health Hazards (acute and chronic): Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.

SECTION 4: FIRST AID MEASURES

- **If inhaled:** May cause irritation; remove from exposure
- If on skin: May cause irritation; wash skin with soap and water
- **If in eyes:** May cause irritation; flush eyes with large quantities of water for at least 15 minutes. If irritation persists after washing, contact a physician.
 - If swallowed: Contact a physician.

SECTION 5: FIRE FIGHTING MEASURES

Suitable/Extinguishing Media

Special Hazards Arising/Forcom Chemical Fire

Special Protective Equiphoeat and Precautions for Fire Fighters:

SECTION 6: ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled:

Personal Precautions, Protective Equipment and/or Emergency Procedures: None

Materials and Methods for Containment and Clean-Up: None

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AND USE:

- **Ventilation:** Local exhaust (if spray applying)
- Precautions for Safe Handling: None
- Conditions for Safe Storage, Including Incompatibilities: None

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

	Ingredients		OSHA	
PEL		ACGIH		

_V			
Silica (Si O	2)	30 mg/m
	7		
Calcium Carbonate	15 mg/m	3	N/A
Frit	N/A	N/A	
Zirconium Silicate	N/A	N/A	
Kaolin/Clay	N/A	N/A	
Nepheline Syenite	N/A	N/A	
Zinc Oxide	15 mg/m	3	2 mg/m
Carboxymethylcellulo	ose N/A	N/A	
Water	N/A	N/A	

- **Engineer Control:** Adequate ventilation (local exhaust) if spray applied.
- Respiratory Protection: Use a NIOSH approved respirator if spray applying.
- Protective Gloves: Not normally needed.
- **Eye Protection:** Wear appropiate eye protection or safety glasses to keep dust out of eyes.
- Other Protective Clothing or Equipment: Wear appropriate clean, protective clothing such as, but not limited to, overalls, smocks, and aprons.
- **Work/Hygienic Practices:** Food, beverages, and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking, smoking, or applying cosmetics.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearancemed and/or Clear Liquids

Odor/Odor Threshold: Neglible PH: N/A
Boiling Point: N/A
Freezing point: 32°F

Freezing point: 32°F
Flash Point: N/A
Vapor Pressure: N/A
Vapor Density: N/A
Flammability: N/A
Evaporation Rate: N/A
Upper/Lower Explosive Nimits:

Partition Coefficient (n-octaeol/water):

Relative Density: N/A
Solubility(ies): N/A
Decompositional Temperature:
Viscosity: N/A

Auto ignition temperatureA

SECTION 10: STABILITY AND REACTIVITY

Reactiv**H**yA

Chemical Stability: Stable

Possibility of Hazardous Beactions:

Conditions to Avoid: Fumes from firing in kiln; Mist created from spray application.

Incompatible Material: None

Hazardous Decomposition By-Products:

SECTION 11: TOXICOLOGY INFORMATION

Primary Route(s) of Entry: Dermal, Inhalation. The highest threat of inhalation exists during dispensing and mixing of dry products, excessive handling of dried, unfired glazed ware and/or during spray application.

Additional information:

These mixtures contain silica, a know carcinogen. **Inhalation** is the only route of entry into the body that can cause Silicosis.

The water-based, premixed products and the dry mix products, when mixed with water, should be non-toxic during recommended use.

Pigments are various metals and metal compounds (may contain one or more of following: tin, iron, zirconium, zinc, cobalt, chromium (III) vanadium, praseodymium, aluminum, cadmium, copper, selenium, manganese).

The risk of exposure to these metals is minimal due to the low percentage used in the glaze formulas. Dermal exposure is negligible as these metals have poor dermal absorption. Inhalation exposure is increased with the use of dry mix products.

Cobalt, and cadmium are considered animal carcinogen. Silica (quartz) is considered a human carcinogen.

Frits are fused silica glass like substances. The bioavailability is limited because of the physical nature of the frit.

These products conform to ASTM-4236 and have been certified by an independent, 3rd party toxicologist to be NON TOXIC.

Mobility Vior Soil:

SECTION 12: ECOLOGICAL INFORMATION

Persistence: Yes
Bioaccumulation: No
Ecotoxicity: None
Other Adverse Effects: None

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Residue/Disposal Methods: None

Safe Handling Information: None

SECTION 14: TRANSPORTATION INFORMATION

UN Shipping Name: N/A UN Number: None

Environmental Hazard: None

Packing Group: None

Transportation Hazard Class: N/A

Special Precautions: None

Not Dangerous for Transport

SECTION 15: REGULATORY INFORMATION

Silica (Quartz), Cobalt and Cadmium are listed by California, Proposition 65, as carcinogenic.

Silica (Quartz), Cobalt and Cadmium are listed on the IARC, OSHA or NTP carcinogen list.

All ingredients are on U.S. TSCA Inventory.

SARA Section 313: None

These products conform to ASTM-4236. Materials have been evaluated under the provisions of LHAMA (Labeling of Hazardous Art Material Act). Products listed on this SDS have been judged to be non-toxic and non-flammable under proposed use conditions. No special warning is required under provisions of LHAMA or California Proposition 65.

SECTION 16: ADDITIONAL INFORMATION

Mayco Glazes do not contain and products and/or ingredients derived from peanuts, eggs, milk, or wheat. Mayco Glazes do not contain latex.

This information is furnished with out warranty, representation, inducement or license of any kind, except that it is accurate to the best of knowledge of COLORAMICS, LLC or obtained from sources believed to be accurate.

COLORAMICS, LLC does not assume any legal responsibility for use or reliance on same. Customers are encouraged to conduct their own tests before using any product. Read the product label.