SLICK 50® PROFESSIONAL ENGINE TREATMENT

1. PRODUCT AND COMPANY IDENTIFICATION

MSDS Number: 15693 Version Date: 10/19/2005

Product Name: SLICK 50® PROFESSIONAL ENGINE TREATMENT

Product Use: Engine treatment **Synonyms:** P-414, 41412016

Company Information

SOPUS Products P.O. Box 4427

Houston, TX 77210-4427

USA

Phone Numbers

Medical Emergency: 1-800-546-6040

Transportation Emergency (USA): 1-800-424-9300

Transportation Emergency (International):

1-703-527-3887(Call Collect)

MSDS Assistance: 1-800-546-6227 Fax On Demand: 1-800-546-6227 Technical Assistance: 1-800-458-4998 Customer Service: 1-800-468-8397 Fax Number: 713-217-3181

Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
BLENDED LUBRICANT	MIXTURE	80 - 98	No
TEFLON DISPERSION	MIXTURE	1 - 5	No

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Other. No information available				
3.HAZARDS IDENTIFICATION				
Emergency and Hazards Overview				
CAUTION:: Contains Petroleum Lubricant.	Repeated skin contact can cause skin disorders.			

Health 1 Flammability 1 Reactivity 0

Primary Route of Exposure: Skin X Inhalation -- Eye --

Health Effect Information

NFPA Ratings:

Othor No information available

Eye Contact: This product is practically non-irritating to the eyes upon direct contact. Based on testing of similar products and/or components.

Skin Contact: Avoid skin contact. This product may cause slight skin irritation upon direct contact. Based on testing of similar products and/or components. Prolonged or repeated skin contact may result in dryness, chapping, and reddening. See Section 11 - Toxicological Information.

Inhalation: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. Shortness of breath and cough are the most common symptoms.

SLICK 50® PROFESSIONAL ENGINE TREATMENT

Ingestion: Do not ingest. This product is relatively non-toxic by ingestion. This product has laxative properties and may result in abdominal cramps and diarrhea. Exposure to a large single dose, or repeated smaller doses, may lead to lung aspiration, which can lead to lipid pneumonia or chronic lung inflammation. These are low-grade, chronic localized tissue reactions.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

Other: No information available

MSDS Number: 15693

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions. No treatment is necessary under ordinary circumstances.

Ingestion: Do not induce vomiting. No treatment is necessary under ordinary circumstances. If victim exhibits signs of lung aspiration such as coughing or choking, seek immediate medical assistance.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: 415.9 F, 213.3 C Test Method: ASTM D 3828-81-Setaflash

Flammable Limits in Air

Upper Percent: No data available **Lower Percent:** No data available

Autoignition Temperature: No data available Test Method: No information available

NFPA Classification: Class III-B combustible liquid

Extinguishing Media: Use dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: No special fire fighting procedures are required.

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: None

Page 2 of 7

SLICK 50® PROFESSIONAL ENGINE TREATMENT

MSDS Number: 15693 Page 3 of 7

Other: No information available

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10.

Regulatory Notifications: No notification required

Containment and Clean up: No special cleanup procedures are necessary. Do not allow spill to enter sewers or watercourses. Small spills may be picked up with absorbent material.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: No special handling procedures are necessary.

Storage: Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials.

Empty Container Warnings

Drums: Not applicable

Plastic: Do not reuse this container. Empty container may retain product residues.

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

This product does not contain any components with OSHA or ACGIH exposure limits.

Personal Protective Equipment

Eye/Face Protection: Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

Skin Protection: Skin protection is not required under conditions of normal use. Launder soiled clothes.

Respiratory Protection: Respiratory protection is not required under conditions of normal use.

Personal Hygiene: Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

Engineering Controls / Work Practices

Ventilation: General room ventilation is normally sufficient.

Other: No information available

MSDS Number: 15693 SLICK 50® PROFESSIONAL ENGINE TREATMENT Page 4 of 7

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber to brown		
Odor: No information available	Vapor Pressure: No data available	
Physical state: Liquid	Vapor Density (air=1): No data available	
pH: No data available	Percent Volatile by Volume: No data available	
Boiling Point: No data available	Volatile Organic Content: No data available	
Melting Point: No data available	Molecular Weight: No data available	
Specific Gravity: 0.88 - 0.9	Average Carbon Number: No data available	
Pour Point: No data available	Viscosity @ 100 F: No data available	
	Viscosity @ 40 C: 80 cSt	
Solubility in Water: No information available		
Octanol / Water Coefficient: Log K_{ow} = No data available		

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: High heat and open flames.

Incompatible Materials to Avoid: May react with strong oxidizing agents.

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Carcinogenicity: The International Agency for Research on Cancer (IARC) has concluded that there is inadequate data to evaluate the carcinogenicity to experimental animals of this class of product. IARC has determined this class of products belongs to Group 3-"not classifiable as to its

carcinogenicity to humans".

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

MSDS Number: 15693 SLICK 50® PROFESSIONAL ENGINE TREATMENT Page 5 of 7

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: No information available

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: Dispose of residual products and empty containers responsibly.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility.

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT) Highway / Rail (Bulk): Not Regulated Highway / Rail (Non-Bulk): Not Regulated

For US shipments, US DOT law requires the shipper to determine the proper shipping description of the material that is being shipped. The shipping information and description contained in this section may not be suitable for all shipments of this material, but may help the shipper determine the proper shipping description for a particular shipment.

International Information

Vessel: IMDG Regulated: -- IMDG Not Regulated: X
Air: ICAO Regulated: -- ICAO Not Regulated: X

Other: No information available

15. Regulatory Information

<u>Regulatory Lists Searched</u>: The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

SLICK 50® PROFESSIONAL ENGINE TREATMENT

MSDS Number: 15693 Page 6 of 7

Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depletors, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

Inventories: 80 - Canada - Domestic substances, 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA , 85 - China Inventory

Regulatory Search Results:

No components appear on any of the regulatory lists searched.

U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.

SARA Section 313: Consumer products are not regulated under SARA, Title III, Section 313.

IARC: No information available

SARA 311 / 312 Categories

Acute: -- Chronic: -- Fire: -- Pressure: -- Reactive: --

Not Regulated: X

Canadian WHMIS Classification

No information available

European Union Classification

Hazard Symbols:

No information available

Risk Phrases:

No information available

Safety Phrases:

No information available

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

Back Label (Updated 2-2003):

WARNING: Continuous contact with used gasoline engine oils has caused skin cancer in animal tests. Avoid prolonged or repeated contact with eyes, skin and clothing. Wash skin with soap and water after handling.

KEEP OUT OF REACH OF CHILDREN.

SLICK 50® PROFESSIONAL ENGINE TREATMENT

MSDS Number: 15693 Page 7 of 7

MSDS Revisions

Previous Version Date: 5/3/2002

Previous Version Information

Section 14: Transportation Information

Other

No information available

Prepared By:

SOPUS Products P.O. Box 4427 Houston, TX 77210-4453 USA

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, SOPUS Products must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information, the results to be obtained from the use thereof, or that any such use do not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.