


Material Safety Data Sheet								
White Traffic Paint (Water Base) Identity (As used on label and list)					Product # 12470			
	Occupational Safety and Health Administration Meets 29 C FR 1910.1200 Standard							
	HMIS Hazard Ratings							
	Health	1		0=Insignificant 1=Slight				
	Flammability	1		2=Moderate 3=High 4=Extreme				
Reactivity	0							
Transportation Information: Proper Shipping Name: Not Regulated								
Hazardous Class: None PKG GRP: None		Ref: N/A		Identification No: None		Label: None required		
SECTION I								
Manufacturer's Name PRIDE Enterprises		Emergency Telephone Number 800-535-5053						
Address 12425 28th Street North, Suite103 St. Petersburg, FL 33716		Telephone Number for Information 727-572-1987		Date Prepared November 7, 1997 Supersedes all previous				
SECTION II - Hazardous Ingredients/Identity Information								
Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS#	% (Optional)	CGIH PPM	TWA MG/M3	ACGIH PPM	STEL MG/M3	SARA Title III	RQ lbs.
Diethylene Glycol Monobutyl Ether (a)	112-34-5	<2					Yes	
Methyl Alcohol (a,b,c,d)	67-56-1	<5	200	260	250	325	Yes	5000
Talc (as silicates)	14807-96- 6			2				
(a) A "Yes" in the SARA Title III column indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-to Know Act of 1986 and of 40 CFR 372.								
(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.								
(c) Indicates the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ this product>20,000 lbs) or greater amounts, according to 40 CFR 302.								
(d) Indicates an employee's skin exposure shall be prevented or reduced to the extent necessary in the circumstances through the use of gloves, coveralls, goggles, or other applicable equipment.								
SECTION III - Physical / Chemical Characteristics								
Boiling Point: 212° F				Specific Gravity (water=1): 1.4621				
Vapor Pressure (mm hg): 17 mm @20° C				Volatile Organic Compounds (VOC's): .86				
Vapor Density (air=1): <1				Evaporation Rate(water=1): <1				
Solubility in water: Dispersible				% Volatile (by wt): 24%				
Appearance & Color: Viscous White Liquid, Characteristic Odor								
SECTION IV - Fire and Explosion Hazard Data								
Flash Point (Method Used): >200° F				Flammability Limits: LEL: N/A UEL: N/A				
Extinguishing Media: CO ₂ ; Water; Water Fog; Dry Chemical; Chemical Foam								
Special Fire Fighting Procedures: Self-contained respiratory equipment; cool containers to								

prevent pressure build up and possible explosion when exposed to extreme heat. **Caution; material will support combustion.**

Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat.

SECTION V - Stability/Reactivity Data

Stability: Unstable: ___ Stable: xxx **Conditions to avoid:** Extreme Temperatures

Incompatibility (Materials to avoid): Strong oxidizers and strong acids

Hazardous Decomposition or Byproducts: Thermal decomposition may yield CO; CO₂

Hazardous Polymerization: May occur: _____ Will not occur: xxx

SECTION VI -Health Hazard Data

Routes of Entry - Signs and Symptoms of Exposure

Emergency and First Aid Procedures

Inhalation: High concentrations are irritating to respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise, blurred vision, coma and death.

Remove victim to fresh air; provide oxygen; administer CPR if victim not breathing; seek medical attention.

Skin: Brief contact may cause slight irritation; prolonged contact may cause moderate reddening, swelling and possible necrosis.

Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; seek medical attention if condition persists.

Eyes: Contact causes severe irritation and pain associated with redness and swelling of the conjunctiva.

Flush eyes with water for 15 minutes while holding eyelids open; get medical attention.

Ingestion: Material is toxic, may cause headaches, dizziness, diarrhea, weakness; large doses may result in red blood cell hemolysis. Methyl alcohol is a systemic poison capable of causing blindness. Symptoms parallel inhalation.

Give 2 glasses of water for dilution; induce vomiting by sticking fingers down throat; never give an unconscious person anything by mouth; seek medical attention.

Health Hazards (Acute and Chronic): Acute effects are possible irritation and discomfort with possible blindness and death; reported chronic effects are marked impairment of vision and enlargement of liver. Product cannot be made nonpoisonous.

Carcinogenicity: NTP? No

IARC Monographs? No

OSHA Regulated: No

Medical conditions generally aggravated by exposure: Pre-existing skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

SECTION VII - Handling and Storage

Steps to be taken in case material is released or spilled: Confine and absorb into approved absorbent; place material into approved containers for disposal; for spills in excess of allowable time (RQ) notify the National Response Center (800) 424-8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313, 40 CFR 372 for reporting requirements.

Waste disposal method: Dispose of in accordance with local, state and federal regulations. Refer to RCRA regulations 40 CFR 372 260-281 for waste disposal instructions; do not flush to sanitary sewer or waterway.

Precautions to be taken in handling and storage: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures.

Other precautions: Keep this and other chemicals out of reach of children; minimize body contact with this product as well as all chemicals in general.

SECTION VIII - Exposure Controls / Personal Protection

Respiratory protection (specific type): None required while threshold limits (Section II) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must

be worn.	
Ventilation: Local exhaust: Required Mechanical (general): Yes	Special: To maintain minimum TWA and STEL levels. Other: Engineering and work controls as required.
Protective gloves: Neoprene or rubber	Eye protection: Goggles with side shields.
Other Protective Clothing/Equipment: Coveralls, apron or other equipment should be worn to minimize skin contact	
Work/Hygienic Practices: Coveralls, apron, or other equipment should be worn to minimize skin contact.	
The information contained herein is believed to be correct. However, PRIDE makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. PRIDE assumes no responsibility for injury from the use of the product described herein.	

