



## Material Safety Data Sheet

Copyright, 2010, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) Hi-Tack 76 Classic Spray Adhesive

**MANUFACTURER:** 3M

**DIVISION:** Industrial Adhesives and Tapes Division

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 05/27/10

**Supersedes Date:** 09/18/09

**Document Group:** 07-7638-5

**Product Use:**

Intended Use: Adhesive  
Specific Use: aerosol adhesive

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
DIMETHYL ETHER	115-10-6	30 - 40
ACETONE	67-64-1	10 - 20
N.J.T.S. Reg No. 04499600-6134P	Trade Secret	10 - 20
CYCLOHEXANE	110-82-7	10 - 20
PENTANE	109-66-0	7 - 13
PROPANE	74-98-6	7 - 13
NAPHTHOL SPIRITS	64742-48-9	0.5 - 1.5
PETROLEUM DISTILLATE	64742-47-8	0.5 - 1.5

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Odor, Color, Grade:** clear, mild solvent odor

**General Physical Form:** Gas aerosol

**Immediate health, physical, and environmental hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Aerosol container contains flammable material under pressure. May cause target organ effects.

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

**Inhalation:**

Intentional concentration and inhalation may be harmful or fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

May be absorbed following inhalation and cause target organ effects.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

**Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** Remove person to fresh air. Get immediate medical attention.

**If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

#### 4.2 NOTE TO PHYSICIANS

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

### SECTION 5: FIRE FIGHTING MEASURES

#### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	<i>No Data Available</i>
Flash Point	-50.00 °F
Flammable Limits - LEL	<i>Not Applicable</i>
Flammable Limits - UEL	<i>Not Applicable</i>

#### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Closed containers exposed to heat from fire may build pressure and explode. Extremely flammable liquid and vapor. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Aerosol container contains flammable material under pressure.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures:

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

### SECTION 7: HANDLING AND STORAGE

**7.1 HANDLING**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children.

**7.2 STORAGE**

Store away from acids. Store away from heat. Store out of direct sunlight.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 ENGINEERING CONTROLS**

Use with appropriate local exhaust ventilation. Use with functioning spray booth or local exhaust. Do not use in a confined area or areas with little or no air movement. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

**8.2.1 Eye/Face Protection**

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields  
Indirect Vented Goggles

**8.2.2 Skin Protection**

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber

**8.2.3 Respiratory Protection**

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece or fullface air-purifying respirator with organic vapor cartridges

. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance.

**8.2.4 Prevention of Swallowing**

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

**8.3 EXPOSURE GUIDELINES**

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
ACETONE	ACGIH	TWA	500 ppm	
ACETONE	ACGIH	STEL	750 ppm	
ACETONE	OSHA	TWA	2400 mg/m3	
CYCLOHEXANE	ACGIH	TWA	100 ppm	
CYCLOHEXANE	OSHA	TWA	1050 mg/m3	
DIMETHYL ETHER	AIHA	TWA	1880 mg/m3	
DIMETHYL ETHER	CMRG	TWA	1000 ppm	
NAPHTHOL SPIRITS	3M	TWA	100 ppm	
NAPHTHOL SPIRITS	CMRG	TWA	300 ppm	

PETROLEUM DISTILLATE	CMRG	TWA	300 ppm
PENTANE	ACGIH	TWA	600 ppm
PENTANE	OSHA	TWA	2950 mg/m3
PROPANE	OSHA	TWA	1800 mg/m3

**SOURCE OF EXPOSURE LIMIT DATA:**

ACGIH: American Conference of Governmental Industrial Hygienists  
 CMRG: Chemical Manufacturer Recommended Guideline  
 OSHA: Occupational Safety and Health Administration  
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Odor, Color, Grade:</b>	clear, mild solvent odor
<b>General Physical Form:</b>	Gas aerosol
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	-50.00 °F
<b>Flammable Limits - LEL</b>	<i>Not Applicable</i>
<b>Flammable Limits - UEL</b>	<i>Not Applicable</i>
<b>Boiling point</b>	<i>Not Applicable</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Specific Gravity</b>	.695 [Ref Std: WATER=1]
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Solubility in Water</b>	Nil
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Hazardous Air Pollutants</b>	0 % weight [Test Method: Calculated]
<b>Volatile Organic Compounds</b>	Approximately 71 %
<b>Kow - Oct/Water partition coef</b>	<i>No Data Available</i>
<b>Percent volatile</b>	Approximately 88 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	Approximately 568 g/l [Test Method: calculated SCAQMD rule 443.1]
<b>Viscosity</b>	<i>Not Applicable</i>

**SECTION 10: STABILITY AND REACTIVITY**

**Stability:** Stable.

**Materials and Conditions to Avoid:**

**10.1 Conditions to avoid**

Heat

**10.2 Materials to avoid**

Strong oxidizing agents

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

The facility should be equipped to handle gaseous waste.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number(s):**

62-4677-4930-5, 62-4677-4935-4, 62-4677-4936-2, CS-0406-6995-5, CS-0406-7020-3

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
CYCLOHEXANE	110-82-7	10 - 20

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
PENTANE	109-66-0	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

### STATE REGULATIONS

Contact 3M for more information.

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**Additional Information:** ++ synthetic polymers, resin, oils, antioxidant and u.v. absorber. Non-hazardous according to Canadian WHMIS criteria. Non-WHMIS controlled.

### INTERNATIONAL REGULATIONS

Non hazardous according to WHMIS criteria.

Contact 3M for more information.

**WHMIS:** Non-hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 4 **Reactivity:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 2

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** 2 **Flammability:** 4 **Reactivity:** 0 **Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

### Revision Changes:

Copyright was modified.

Section 8: Eye/face protection information was modified.

Section 8: Skin protection - recommended gloves information was modified.

Section 8: Respiratory protection - recommended respirators information was modified.

Section 9: Property description for optional properties was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 10.1 Conditions to avoid heading was added.

Section 10.2 Materials to avoid heading was added.

Section 10: Materials to avoid physical property was added.

Section 10: Conditions to avoid physical property was added.

Section 6: Release measures information was deleted.

Section 10: Materials and conditions to avoid physical property was deleted.

Section 8: Exposure guidelines legend was deleted.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



**3M MSDSs are available at [www.3M.com](http://www.3M.com)**