Product ID:40 37505 ZIP DRY CLEAR BASE MSDS Date:03/18/1986 FSC:8030 NIIN:00F030605 MSDS Number: BSLKD === Responsible Party === Company Name: VALSPAR CORPORATION Address:1101 THIRD STREET SOUTH City:MINNEAPOLIS State:MN ZIP:55413-1211 Country:US Info Phone Num: 612-332-7371 Emergency Phone Num:800-228-5635 CAGE:06758 === Contractor Identification === Company Name: VALSPAR CORPORATION Address:1101 THIRD STREET SOUTH City:MINNEAPOLIS State:MN ZIP:55415 Country:US Phone: 800-228-5635 CAGE:06758 Company Name: VALSPAR CORPORATION Address:1101 THIRD ST. SOUTH Box:City:MINNEAPOLIS State:MN ZIP:55415 Country:US Phone: 612-332-7371/888-345-5732 CAGE:23526 Ingred Name: V M & P NAPHTHA, LIGROINE, MINERAL SPIRITS CAS:8032-32-4 RTECS #:016180000 Other REC Limits:STEL 400 PPM ACGIH TLV:300 PPM Ingred Name: BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHTHA CAS:8030-30-6 RTECS #:DE3030000 Other REC Limits:STEL 400 PPM OSHA PEL:100 PPM ACGIH TLV:100 PPM Ingred Name:KEROSENE, KEROSINE CAS:8008-20-6 RTECS #:0A5500000 Other REC Limits: 100 MG/CUM NIOSH ACGIH TLV:200 PPM Ingred Name: ETHYLENE GLYCOL PROPYL ETHER, EKTASOLVE EP CAS:2807-30-9 RTECS #:KM2800000

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: IRRITATION. INHALATION: RESPIRATORY IRRITATION. OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. Explanation of Carcinogenicity:NONE Effects of Overexposure: INHALATION: DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS. First Aid: INHALATION: REMOVE TO FRESH AIR. IF NECESSARY, USE MOUTH-TO-MOUTH. SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES. Flash Point Method:TCC Flash Point:55F Lower Limits:1.2% Upper Limits:15.8% Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS OR AIR MASKS. CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL W/WATER SPRAY. Spill Release Procedures: VENTILATE AREA. AVOID BREATHING OF VAPORS. USE SCBA OR AIRMASK FOR LARGE SPILLS IN A CONFINED AREA. ELIMINATE IGNITION SOURCES. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS. AVOID CONTACT W/EYES. Handling and Storage Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF FEW INCHES. KEEP AWAY FROM IGNITION SOURCES/TEMPS >120F. Other Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE, INCLUDING FLAMMABLE/EXPLOSIVE VAPORS. DON'T CUT/PUNCTURE/WELD ON/NEAR CONTAINER. OBSERVE ALL LABEL WARNING. INTENTI ONAL MISUSE MAY BE HARMFUL/FATAL. Respiratory Protection: WEAR APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) DURING & AFTER APPLICATION UNLESS AIR MONITORING VAPOR/MIST LEVELS ARE BELOW APPLICABLE LIMITS. Ventilation: REQUIRED FOR SPRAYING IN CONFINED AREA, VENTILATION EQUIPMENT SHOULD BE EXPLOSION PROOF. Protective Gloves:REQUIRED Eye Protection:REQUIRED Supplemental Safety and Health Boiling Pt:B.P. Text:240F Vapor Pres:1.3 Vapor Density:5.52 Spec Gravity:0.91 Evaporation Rate & Reference: (BU AC = 1): 0.22 Solubility in Water: INSOLUBLE Appearance and Odor: WHITE LIQUID, ODOR NORMAL FOR COATINGS PRODUCT. Percent Volatiles by Volume:65.57

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:IGNITION SOURCES, TEMPS >120F Hazardous Decomposition Products:HALIDES, CO2, CO, METAL OXIDES

Waste Disposal Methods:DISPOSE OF IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES W/LOCAL, STATE, & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.