MSDS NAME: MOORWOOD EXTERIOR SOLID WOOD STAIN, 080 NIIN:00N009067 MSDS Number: BCRNN === Responsible Party === Company: BENJAMIN MOORE & CO. Address:51 CHESTNUT RIDGE RD. City:MONTVALE State:NJ ZIP:07645 Info Phone Num:201-344-1200 Emergency Phone Num: 201-344-1200 CAGE:09585 === Contractor Identification === Company: BENJAMIN MOORE & CO Address:51 CHESTNUT RIDGE RD City:MONTVALE State:NJ ZIP:07645 Country:US Phone: 201-573-9600 CAGE:09585 Company: BENJAMIN MOORE & CO Address:51 CHESTNUT RIDGE RD Box:City:MONTVALE State:NJ ZIP:07645 Country:US Phone: 201-573-9600 CAGE:91950 Name:MINERAL SPIRITS.VAPOR PRESSURE:<5.0 MMHG AT 100F,38C. CAS:64742-86-5 RTECS #:LX3296500 Fraction by Wt: 30-37% Other REC Limits:N/K OSHA PEL:500 PPM TWA (MFR) ACGIH TLV:100 PPM TWA (MFR) LD50 LC50 Mixture:N/K Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: REPORTS HAVE ASSOCIATED PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE WITH REPEATED PROLONGED OVEREXPOSURE TO SOLVENTS AMONG PERSONS ENGAGED IN THE PAINTING TRADE. Explanation of Carcinogenicity:N/K Effects of Overexposure:EYES:PRIMARY IRRITATION.SKIN:PRIMARY IRRITATION.INGESTION:N/K .INHALATION:RESPIRATORY IRRITATION AND CENTRAL NERVOUS SYSTEM EFFECT-ANESTHETIC.

Eyes: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH MILD SOAP AND WATER.INGESTION:N/K .INHALATION:REMOVE FROM AREA, MAINTAIN BREATHING, CALL PHYSICIAN. Flash Point:113F,45C Lower Limits:1.0% Upper Limits:N/K Extinguishing Media: FOAM, CO*2, DRY CHEMICAL, WATER FOG. Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .DO NOT USE WATER STREAM ON BURNING LIQUID.COOL EXPOSED CONTAINERS WITH WATER. Unusual Fire/Explosion Hazard: HAZARDOUS DECOMPOSITION PRODUCTS: BURNING MAY PRODUCE CARBON DIOXIDE AND CARBON MONOXIDE. Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS.USE NON-SPARKING TOOLS TO RETURN MATERIALS TO CONTAINER.ABSORB RESIDUE WITH FULLER'S EARTH. Neutralizing Agent:N/K Handling and Storage Precautions: COMBUSTIBLE-KEEP AWAY FROM HEAT AND FLAME.USE ADEQUATE VENTILATION.CLOSE CONTAINER AFTER EACH USE.KEEP OUT OF REACH OF CHILDREN. Other Precautions: AVOID SKIN CONTACT AND BREATHING OF VAPOR OR SPRAY MIST.DO NOT TAKE INTERNALLY.DELIBERATELY CONCENTRATION AND INHALATION OF CONTENTS MAY BE HARMFUL OR FATAL. ======= Exposure Controls/Personal Protection ========== Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . Ventilation:LOCAL AND GENERAL VENT NECESSARY TO KEEP AIR CONC BELOW TLV .DISCHARGE EXHAUST AWAY FROM IGNITION SOURCES. Protective Gloves: REQUIRED DURING REPEATED CONTACT. Eye Protection: CHEMICAL WORKERS GOGGLES . Other Protective Equipment: CLOTHING ADEQUATE TO PROTECT SKIN. Supplemental Safety and Health BOILING RANGE: 313-388F, 156-197C. SPECIFIC GRAVITY: 1.2-1.3 (WATER=1). Boiling Pt:B.P. Text:(SEE SUPP) Melt/Freeze Pt:M.P/F.P Text:N/K Decomp Temp:Decomp Text:N/K Vapor Pres:N/K Vapor Density:>AIR Spec Gravity:(SEE SUPP DATA) Evaporation Rate & Reference:SLOWER THAN ETHER Solubility in Water:N/K Appearance and Odor:LIQUID Percent Volatiles by Volume:51-56

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

*** END OF RECORD ***