

MATERIAL SAFETY DATA SHEET

SECTION 1 – PRODUCT INFORMATION

PRODUCT NAME: Roberts 7200 Solvent Free Cove Base Adhesive
Roberts MSDS Code #: 7200C
PRODUCT USES: Adhesive for installing cove base

W.H.M.I.S. CLASSIFICATION: NON-CONTROLLED
HMIS Rating: 1H 0F 0R PPE B
V.O.C. CONTENT: < 1 gram / liter

MANUFACTURER'S NAME: Roberts Consolidated Industries
ADDRESS: 300 Cross Plains Blvd. Dalton, GA 30721
24 HOUR (CANUTEC) PHONE: (613) 996-6666

Phone: (706) 277-5294

SECTION 2 – PREPARATION INFORMATION

PREPARED BY: Technical Dept.
INFORMATION PHONE: Roberts/QEP Canada Ltd. (905) 791-4444
SOURCES USED: Raw material supplier M.S.D.S.
DATE REVISED: Jan. 7, 2010

SECTION 3 - HAZARDOUS INGREDIENTS

COMPONENT	APPROX. %	UN#	CAS#	LD50	LC50
NO REPORTABLE INGREDIENTS					

SECTION 4 – PHYSICAL DATA

BOILING POINT: 100° C
VAPOUR DENSITY (AIR=1): Heavier than air
VAPOUR PRESSURE (MM OF MERCURY): As for water.
SOLUBILITY IN WATER: Miscible
APPEARANCE AND ODOUR: Light tan heavy paste, very mild odour.

SPECIFIC GRAVITY (H2O=1): 1.2
pH: 9.0-9.4
EVAPORATION RATE (BUTYL ACETATE=1): Slower
EVAPORATION RATE (ETHYL ACETATE=1): Slower
PERCENT VOLATILE: 40-44
ODOUR THRESHOLD (PPM): Not available

SECTION 5 - FIRE AND EXPLOSION DATA

FLASHPOINT (specify method): N/A
FLAMMABLE LIMITS (% BY VOLUME): LOWER: N/A UPPER: N/A
FIRE EXTINGUISHING MEDIA: Foam, CO₂, Dry Chemical
SPECIAL FIRE-FIGHTING PROCEDURES: Self-contained breathing apparatus should be worn for fires involving this product.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None

METHOD USED:

IMPACT SENSITIVITY: Insensitive

SENSITIVITY TO STATIC DISCHARGE: Insensitive

TDG FLAMMABILITY CLASSIFICATION: Not regulated.

SECTION 6 - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY (Materials to avoid): Strong oxidizers and caustics
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂, and Hydrocarbons upon combustion.
HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Excessive Heat

CONDITIONS TO AVOID: None

SECTION 7 – TOXICOLOGICAL PROPERTIES

ENTRY ROUTE TABLE

SKIN CONTACT	X	SKIN ABSORPTION	EYE CONTACT	X	INHALATION ACUTE	INHALATION CHRONIC	INGESTION	X
--------------	---	-----------------	-------------	---	------------------	--------------------	-----------	---

EFFECTS OF ACUTE EXPOSURE TO MATERIAL: Product may irritate eyes and skin. Ingestion causes vomiting, diarrhea, depressed respiration.

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: Skin chapping.

LD50 (SPECIFY SPECIES & ROUTE):	LC50 (SPECIFY SPECIES):	EXPOSURE LIMIT:	IRRITANCY:
Not available	Not available	Not available	None
SENSITIZING CAPACITY:	CARCINOGENICITY:	REPRODUCTIVITY EFFECTS:	SYNERGISTIC MATERIALS:
None	None	None	None known

SECTION 8 – PREVENTATIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): None required.

VENTILATION: None should be required.

PROTECTIVE GLOVES: Polyethylene, PVC, natural rubber if skin contact

EYE PROTECTION: Goggles

OTHER PROTECTIVE EQUIPMENT: None required.

SPILL PROCEDURES: Mechanically collect. Wash area with water. Prevent from entering sewers or waterways. Spilled material may cause slippery conditions. Promptly report significant spills to appropriate authorities. Consult local regulations.

WASTE DISPOSAL METHOD: Destroy by incineration at an approved facility. Dried material only may be landfilled. Consult local regulations.

STORAGE & HANDLING PRECAUTIONS: Keep containers from excessive heat and freezing. Keep containers closed when not in use. Keep out of reach of children.

OTHER PRECAUTIONS: None.

SECTION 9 – FIRST AID MEASURES

EYES: Flush with water for 20 minutes, holding eyelids open. Seek medical attention.

SKIN: Wash with soap and water. Seek medical attention if irritation develops.

INGESTION: Do not induce vomiting. If victim is conscious, give milk or water. Contact physician immediately.