

Material Safety Data Sheet

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

PRODUCT NAME: 3M Scotch(R) Permanent Purple Glue Stick & White Permanent Glue Stick

MANUFACTURER: 3M

DIVISION: Stationery & Office Supplies

ADDRESS: 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 05/17/2004 **Supercedes Date:** 05/21/2003

Document Group: 16-4455-8

ID Number(s):

70-0710-9719-3, 70-0711-8006-4, 70-0712-1746-0

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

09-4549-3, 09-4555-0

Revision Changes: Copyright was modified.

Kit: ID number(s) was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may

3M MATERIAL SAFETY DATA SHEET 3M Scotch(R) Permanent Purple Glue Stick & White Permanent Glue Stick 05/17/2004

have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.



Material Safety Data Sheet

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SCOTCH BRAND Permanent White Glue Stick 6008, 6015, 6020, 6036, 6040, 003, 0038

MANUFACTURER: 3M

DIVISION: Stationery Products

ADDRESS: 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 05/12/09 Supercedes Date: 12/19/08

Document Group: 09-4549-3

Product Use:

Intended Use: Adhesive

SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	% by Wt
WATER	7732-18-5	60 - 65
N-VINYLPYRROLIDINONE POLYMER	9003-39-8	14 - 16
SUCROSE	57-50-1	7 - 9
POLYETHYLENE GLYCOL	25322-68-3	6 - 8
SODIUM STEARATE	822-16-2	5 - 7
SODIUM HYDROXIDE	1310-73-2	0.4 - 0.6

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: White with fatty acid/acrylic odor.

General Physical Form: Solid

Immediate health, physical, and environmental hazards:

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

No health effects are expected.

Ingestion:

No health effects are expected.

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: No need for first aid is anticipated.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot ApplicableOSHA Flammability Classification:Not Applicable

5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire.

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Page 2 of 7

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Ventilate the area with fresh air. Collect as much of the spilled material as possible. Clean up residue with detergent and water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact.

7.2 STORAGE

Store under normal warehouse conditions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

8.2.2 Skin Protection

Not applicable.

8.2.3 Respiratory Protection

Not applicable.

8.2.4 Prevention of Swallowing

Do not ingest.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	Authority	<u>Type</u>	<u>Limit</u>	Additional Information
N-VINYLPYRROLIDINONE POLYMER	CMRG	TWA, as respirable	5 mg/m3	
		dust		
N-VINYLPYRROLIDINONE POLYMER	CMRG	TWA, as total dust	10 mg/m3	

POLYETHYLENE GLYCOLS	AIHA	TWA, as aerosol	10 mg/m3	
SODIUM HYDROXIDE	ACGIH	CEIL	2 mg/m3	
SODIUM HYDROXIDE	CMRG	TWA	2 mg/m3	
SODIUM HYDROXIDE	OSHA	CEIL	2 mg/m3	Table Z-1A
SODIUM HYDROXIDE	OSHA	TWA	2 mg/m3	Table Z-1
STEARATES	ACGIH	TWA, as total dust	10 mg/m3	Table A4
SUCROSE	ACGIH	TWA	10 mg/m3	Table A4
SUCROSE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
SUCROSE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Paste

Odor, Color, Grade: White with fatty acid/acrylic odor.

General Physical Form: Solid

Autoignition temperature Not Applicable Flash Point Not Applicable Not Applicable Flammable Limits - LEL Not Applicable Flammable Limits - UEL Not Applicable **Boiling point** 0.95 - 1 g/cm3 **Density** Vapor Density Not Applicable **Vapor Density** Not Applicable Vapor Pressure Not Applicable Vapor Pressure Not Applicable

Specific Gravity 0.95 - 1.0 [Ref Std: WATER=1]

pH Approximately 10.3 Units not avail. or not appl.

Melting point Approximately 140 °F

Solubility in WaterAppreciableEvaporation rateNot ApplicablePercent volatile60 - 65 % weightViscosityNot Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

Page 4 of 7

<u>Substance</u> Carbon monoxide Carbon dioxide Condition

During Combustion During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

 $41\text{-}3700\text{-}5412\text{-}8, 41\text{-}3700\text{-}5422\text{-}7, 44\text{-}0028\text{-}8703\text{-}0, 44\text{-}0040\text{-}0578\text{-}9, 44\text{-}0040\text{-}1352\text{-}8, 44\text{-}0040\text{-}1353\text{-}6, 44\text{-}0040\text{-}1354\text{-}4, 44\text{-}0040\text{-}1355\text{-}1, 44\text{-}0040\text{-}5915\text{-}8, 44\text{-}0040\text{-}5915\text{-}8, 44\text{-}0040\text{-}5916\text{-}6, 44\text{-}0040\text{-}5917\text{-}4, 44\text{-}0040\text{-}5918\text{-}2, 70\text{-}0050\text{-}3211\text{-}8, 70\text{-}0050\text{-}3431\text{-}2, 70\text{-}0709\text{-}7778\text{-}3, 70\text{-}0709\text{-}7779\text{-}1, 70\text{-}0709\text{-}7781\text{-}7, 70\text{-}0709\text{-}7821\text{-}1, 70\text{-}0709\text{-}9201\text{-}4, 70\text{-}0709\text{-}9872\text{-}2, 70\text{-}0710\text{-}2681\text{-}2, 70\text{-}0710\text{-}2705\text{-}9, 70\text{-}0710\text{-}2733\text{-}1, 70\text{-}0710\text{-}3228\text{-}1, 70\text{-}0710\text{-}3366\text{-}9, 70\text{-}0710\text{-}3425\text{-}3, 70\text{-}0710\text{-}3459\text{-}2, 70\text{-}0710\text{-}6564\text{-}6, 70\text{-}0710\text{-}8060\text{-}3, 70\text{-}0710\text{-}8951\text{-}3, 70\text{-}0711\text{-}5483\text{-}8, 70\text{-}0711\text{-}7720\text{-}1, 70\text{-}0711\text{-}7786\text{-}2, 70\text{-}0711\text{-}7815\text{-}9, 70\text{-}0711\text{-}7816\text{-}7, 70\text{-}0712\text{-}0526\text{-}7, 70\text{-}0712\text{-}0712\text{-}0712\text{-}0712\text{-}0712\text{-}3, 70\text{-}0712\text{-}0712\text{-}1782\text{-}5, 70\text{-}0712\text{-}1537\text{-}3, 70\text{-}0712\text{-}1574\text{-}6, 70\text{-}0712\text{-}1590\text{-}2, 70\text{-}0712\text{-}1593\text{-}6, 70\text{-}0712\text{-}1594\text{-}4, 70\text{-}0712\text{-}1599\text{-}3, 70\text{-}0712\text{-}1782\text{-}5, 70\text{-}0712\text{-}1806\text{-}2, 70\text{-}0713\text{-}0376\text{-}5, 70\text{-}0713\text{-}0555\text{-}4, 70\text{-}0713\text{-}0659\text{-}4, 70\text{-}0713\text{-}0659\text{-}4, 70\text{-}0713\text{-}0660\text{-}2, 70\text{-}0713\text{-}0661\text{-}0, 70\text{-}0713\text{-}0727\text{-}9, 70\text{-}0713\text{-}0728\text{-}7, 70\text{-}0713\text{-}0775\text{-}8, 70\text{-}0713\text{-}0775\text{-}6, 70\text{-}0713\text{-}0659\text{-}4, 70\text{-}0713\text{-}0660\text{-}2, 70\text{-}0713\text{-}0661\text{-}0, 70\text{-}0713\text{-}04898\text{-}4, 70\text{-}0713\text{-}4977\text{-}6, 70\text{-}0713\text{-}5809\text{-}8, 70\text{-}0713\text{-}5809\text{-}8, 70\text{-}0713\text{-}5809\text{-}8, 70\text{-}0713\text{-}5809\text{-}8, 70\text{-}0713\text{-}5809\text{-}8, 70\text{-}0713\text{-}8169\text{-}6, 70\text{-}0713\text{-}8159\text{-}6, 70\text{-}0713\text{-}9128\text{-}1, 70\text{-}0713\text{-}9201\text{-}6, 70\text{-}0713\text{-}9381\text{-}6, 70\text{-}0713\text{-}9424\text{-}9, 70\text{-}0713\text{-}9508\text{-}4, 70\text{-}0713\text{-}8169\text{-}6, 70\text{-}0713\text{-}9121\text{-}6, 70\text{-}0713\text{-}9128\text{-}1, 70\text{-}0713\text{-}9201\text{-}6, 70\text{-}0713\text{-}9381\text{-}6, 70\text{-}0713\text{-}9424\text{-}5, 70\text{-}0713\text$

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 0 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Page 6 of 7

Revision Changes: Copyright was modified. Section 14: ID Number(s) Template 1 was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com



Material Safety Data Sheet

Copyright, 2007, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SCOTCH BRAND Permanent Purple Glue Stick 6108, 6110, 6115

MANUFACTURER: 3M

DIVISION: Stationery Products

ADDRESS: 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 05/30/2007 **Supercedes Date:** 03/29/2006

Document Group: 09-4555-0

Product Use:

Intended Use: Adhesive

SECTION 2: INGREDIENTS

Ingredient	<u>C.A.S. No.</u>	% by Wt	
WATER	7732-18-5	60 - 65	
N-VINYLPYRROLIDINONE POLYMER	9003-39-8	14 - 16	
SUCROSE	57-50-1	7 - 9	
POLYETHYLENE GLYCOL	25322-68-3	6 - 8	
SODIUM STEARATE	822-16-2	5 - 7	
ETHYL ALCOHOL	64-17-5	< 1	

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Purple with fatty acid/acrylic odor.

General Physical Form: Solid

Immediate health, physical, and environmental hazards:

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

3M MATERIAL SAFETY DATA SHEET SCOTCH BRAND Permanent Purple Glue Stick 6108, 6110, 6115 05/30/2007

Contact with the eyes during product use is not expected to result in significant irritation.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Inhalation:

No health effects are expected.

Ingestion:

No health effects are expected.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

NOTE: This product contains ethanol. In IARC published Monograph No. 44, entitled, "Alcohol Drinking", the carcinogenicity of ethanol was determined based on chronic exposure to ethanol through human consumption of alcoholic beverages. This is not an expected effect during the foreseeable use of this product.

IngredientC.A.S. No.Class DescriptionRegulationETHYL ALCOHOL64-17-5Group 1International Agency for Research on Cancer

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Flush eyes with water. Call a physician.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

Inhalation: No need for first aid is anticipated.

If Swallowed: No need for first aid is anticipated.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

5.2 EXTINGUISHING MEDIA

Non-combustible. Choose material suitable for surrounding fire.

Page 2 of 7

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Ventilate the area with fresh air. Collect as much of the spilled material as possible. Clean up residue with detergent and water. Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Avoid eye contact with dust or airborne particles.

7.2 STORAGE

Store under normal warehouse conditions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Not applicable.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact.

8.2.2 Skin Protection

Not applicable. Gloves are not required.

8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

8.2.4 Prevention of Swallowing

Not applicable.

8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	Authority	Type	<u>Limit</u>	Additional Information
ETHYL ALCOHOL	ACGIH	TWA	1000 ppm	Table A4
ETHYL ALCOHOL	OSHA	TWA	1000 ppm	Table Z-1
N-VINYLPYRROLIDINONE POLYMER	CMRG	TWA, as respirable	5 mg/m3	
		dust		
N-VINYLPYRROLIDINONE POLYMER	CMRG	TWA, as total dust	10 mg/m3	
POLYETHYLENE GLYCOLS	AIHA	TWA, as aerosol	10 mg/m3	
STEARATES	ACGIH	TWA, as total dust	10 mg/m3	Table A4
SUCROSE	ACGIH	TWA	10 mg/m3	Table A4
SUCROSE	OSHA	TWA, respirable	5 mg/m3	Table Z-1
SUCROSE	OSHA	TWA, as total dust	15 mg/m3	Table Z-1

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form: Paste

Odor, Color, Grade: Purple with fatty acid/acrylic odor.

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot ApplicableBoiling pointNot ApplicableDensity0.95 - 1 g/cm3Vapor DensityNot Applicable

Vapor Pressure Not Applicable

Specific Gravity 0.95 - 1.0 [Ref Std: WATER=1]

pH 10.3

Melting point Approximately 90 °F

Solubility in WaterAppreciableEvaporation rateNot ApplicablePercent volatile60 - 65 % weightViscosityNot Applicable

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

Page 4 of 7

Hazardous Decomposition or By-Products

Substance

Condition

Carbon monoxide Carbon dioxide During Combustion
During Combustion

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14:TRANSPORT INFORMATION

ID Number(s):

 $44-0028-8704-8,\ 44-0040-0579-7,\ 44-0042-4702-7,\ 70-0709-7783-3,\ 70-0709-7784-1,\ 70-0709-7785-8,\ 70-0709-7818-7,\ 70-0709-8063-9,\ 70-0709-8724-6,\ 70-0709-9965-4,\ 70-0710-1985-8,\ 70-0710-2281-1,\ 70-0710-2426-2,\ 70-0710-2863-6,\ 70-0710-2864-4,\ 70-0710-2865-1,\ 70-0710-2866-9,\ 70-0710-2894-1,\ 70-0710-2902-2,\ 70-0710-3227-3,\ 70-0710-3270-3,\ 70-0710-3367-7,\ 70-0710-3446-9,\ 70-0710-3460-0,\ 70-0710-6565-3,\ 70-0710-8755-8,\ 70-0710-8756-6,\ 70-0710-8984-4,\ 70-0710-8985-1,\ 70-0711-7784-7,\ 70-0712-1595-1,\ 70-0712-1596-9,\ 70-0713-0642-0,\ 70-0713-0674-3,\ 70-0713-4943-8,\ 70-0714-2262-3,\ 70-0714-2263-1,\ 70-0714-8350-0$

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

STATE REGULATIONS

Contact 3M for more information.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

 $\textbf{Health:} \ 0 \quad \textbf{Flammability:} \ 0 \quad \textbf{Reactivity:} \ 0 \quad \textbf{Special Hazards:} \ None$

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 1: Product use information was modified.

Section 1: Division name was modified.

Copyright was modified.

Section 13: Waste disposal method information was modified.

Section 3: Carcinogenicity phrase was modified.

3M MATERIAL SAFETY DATA SHEET SCOTCH BRAND Permanent Purple Glue Stick 6108, 6110, 6115 05/30/2007

Section 2: Ingredient table was modified. Section 14: ID Number(s) was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 5: OSHA flammability heading was deleted.

Section 5: OSHA flammability data was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

Page 7 of 7