EASTMAN KODAK COMPANY -- 146 4643, SELECTOL DEVELOPER -- 6750-00K001069

Product ID:146 4643, SELECTOL DEVELOPER MSDS Date:01/01/1985 FSC:6750 NIIN:00K001069 MSDS Number: BCCDL === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num: 716-722-5151 Emergency Phone Num: 716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone: 716-722-5151/(800) 242-2424 CAGE:19139 Ingred Name:HYDROQUINONE (SARA III) CAS:123-31-9 RTECS #:MX3500000 Fraction by Wt: 12.5% OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name: P-METHYLAMINOPHENOL SULFATE; CAS# 55-55-0; WT% RANGE 1-5% CAS:55-55-1 RTECS #:SL8650000 Fraction by Wt: 3% Ingred Name:NON-HAZARDOUS INGREDIENTS Fraction by Wt: 84.5% Effects of Overexposure:EYES:IRRITNT; INHALE/SKIN:MAY CAUSE IRRITATION; REPEATED SKIN CONTACT MAY CAUSE ALLERGIC SKIN REACTION First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF NEED:EYES:FLUSH W

LG AMTS H*20 FOR 15 MIN; SKIN: FLUSH W LG AMTS H*20; INGEST: RINSE

MOUTH; GET IMMEDIATE MEDICAL ATTENTION FOR EYES OR INGEST. Extinguishing Media:SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP. Unusual Fire/Explosion Hazard:NONE NOTED: IF DUSTING CONDITIONS, USE H*20 SPRAY TO KNOCK DOWN DUST (IRRITNT). Spill Release Procedures: EVACUATE UNPROTECTED PERSONS.PROVIDE VENTILATION/ELIM DUST.SWEEP/SHOVEL MATERIAL INTO COVERED CONTAINERS PENDING DISPOSAL.RESIDUE MAY BE FLUSHED WITH WATER. Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED, LOW FIRE RISK AREA.PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL. REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT HYGIENE.USE OF NON-ALKALINE (ACID) TYPE HAND CLEANER REDUCES ALLERGIC SKIN REACTION RISK. Respiratory Protection: FOR EXCESSIVE DISPERSAL, IN AIR, WEAR DUST RESPIRATOR. Ventilation: MECHANICAL (GEN./LOCAL EXHAUST AS NECESSARY) Protective Gloves: IMPERVIOUS Eye Protection: SAFETY GLASSES, IF REQD Other Protective Equipment: NO SPECIAL REQUIREMENTS EXCEPT TO PREVENT SKIN CONTACT. Supplemental Safety and Health MSDS FROM MFG.DATED 10-4-79, REISSUED 12/79. HCC:N1 Vapor Pres:0 Spec Gravity:>1 Solubility in Water: APPRECIABLE Appearance and Odor:WHITE POWDER; ODORLESS Percent Volatiles by Volume:0 Stability Indicator/Materials to Avoid:YES MINERAL ACIDS Stability Condition to Avoid: DUST GENERATING CONDITIONS. Hazardous Decomposition Products:SULFUR DIOXIDE Waste Disposal Methods: KEEP IN COVERED CONTAINERS PENDING DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE

INTERNATIONAL, FEDERAL, STATE & LOCAL REGULATIONS.MFG NOTES MATERIAL MAY BE FLUSHED TO SEWER WITH EXCE SS OF WATER; OR DISPOSED IN LANDFILL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.